Datos técnicos

5010-1L | Aceite de silicona, tipo 200-05, 1 litro (rango útil:

Descripción general del producto: 5010-1L | Aceite de silicona, tipo 200-05, 1 litro (rango útil:

Silicone oil is used as a calibration media in temperature controlled baths. Different types of silicone oil are chosen for specific temperature ranges based on their viscosity at those temperatures. They have good thermal characteristics and low flammability.

- Silicone oil bath fluid type 200.05
- Usable range: -40 °C to 130 °C
- FlashPoint: 133 °C

Atmospheric pressure affects the usable range of some fluids. The temperatures quoted are at sea level. Flash point is the temperature at which a vapor (not the fluid) will ignite if exposed to an open flame. When the flame is removed, the vapor will stop burning. (Open cup method).

Modelos

5010-3.8L

Aceite de silicona, tipo 200-05, 1 litro (rango útil:

Fluke. *Manteniendo su mundo en marcha.*

Fluke Corporation
Everett, WA 98206 EE.UU.

Para obtener información adicional En EE. UU.
(800) 443-5853
En Europa/Medio Oriente/África
+31 (0)40 267 5100
En Canadá (800)-36-FLUKE
www.fluke.com

Latin America
Tel: +1 (425) 446-5500
www.fluke.com/es-co
©2025 Fluke Corporation. Reservados todos los derechos. Impreso en los Países Bajos. Información sujeta a modificación sin previo aviso.
03/2025

No está permitido modificar este documento sin autorización por escrito de Fluke Corporation.