

2x16 AWG PP 300V OFS FPLR Fire Alarm & Control Cable

POWER & CONTROL

P/N 5F161S2103

INDUSTRY

Applications

Short-range low-frequency signals, Fire alarm, Indoor




Outer Jacket Material
FR-PVC



Outer diameter
4.5 mm nom.



Weight
38 kg/km



General Construction

One shielded twisted pair is jacketed.
Cable passes UL Riser Flame test.

Design & Materials

Conductor Material	Annealed Bare Copper
Conductor Size (AWG)	16
Conductor Size (mm)	1.29
Conductor Construction	Solid
Insulation Material	PP
Insulation O.D. (mm nom)	1.7
Conductor Color Code	Red x Black
Binder	Polyester
Overall Shield Design	100% Coverage
Overall Shield Material	Aluminum/Polyester Foil
Overall Drain-wire Material	Annealed Tinned Copper
Overall Drain-Wire Size (AWG)	24
Overall Drain-wire Construction	Solid
Total Number Of Conductors	2
Outer Jacket Thickness (mm nom)	0.5
Outer Jacket Color	Red
Marking	Per request

2x16 AWG PP 300V OFS FPLR Fire Alarm & Control Cable

P/N 5F161S2103

INDUSTRY

Performance

Max. DC Resistance ($\Omega/\text{km}@20^{\circ}\text{C}$)	13.1
Mutual Capacitance - Core to Core (pF/m)	215
Inductance	0.5
Dielectric Strength (V/minute)	2000
Dielectric Strength to Shield (V/minute)	1000
Voltage Rating (V)	300
Min. Bend Radius (mm)	Dx6
Min. Operating Temperature ($^{\circ}\text{C}$)	-15
Max. Operating Temperature ($^{\circ}\text{C}$)	+75

Standards

Flammability Rating
UL CMR

Applicable Standards
RoHS 3 2015/863/EU



Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Version 1.4 | Last update: 2016-04-04